SCREEN DRYING CABINETS

DC-513610





Options

- · Stainless steel shelves for rustproof drying
- Digital temperature control

HEAVY DUTY Industrial stainless steel finned heater

CAPACITY Holds up to (20) 25" x 36" (63.6 x 91.4 cm) or

up to (10) 51" x 36" (129.5 x 91.4 cm)

POWERFUL One (1) 290 CFM (8.5 CMM) air flow blower

CONSISTENT Pressurized cabin with positive air flow keeps out

contaminants even if an air leak occurs

EFFECTIVE Screens sit horizontal on removable shelves (angled

to provide edge contact only)

FAST Dries fully loaded cabinet in as quickly as 40 minutes*

EFFICIENT 4" (10 cm) exhaust duct for contaminated air removal

PRECISE Light tight heavy duty double wall

E4731/VDC-513610

combo (As shown):

EASY Simple to clean or replace filtered air intake

VDC-513610 and E4731 Combo Perfect for exposing and drying your DiGiT Numbering Screens up to 12"!!

The VDC-513610 is capable of drying (20) 25" x 36" screens or (10) 51" x 36" screens. The unique positionable center tree

accommodate all these sizes and more!



and 47" x 31" screens.



Shown with center tree installed and 20" x 24" screens.

*Drying times will vary. Humidity, thickness and type of emulsion used, and size of screens are factors in Dri-Vault curing time.





Exposing Units

Technical Specifications

| MADE IN U.S.A. | E2-2124 (LED) E1-2124 (Fluorescent) | E2-2331 (LED) E2331 (Fluorescent) | E2-4731 (LED) E4731 (Fluorescent) | E2-4131 (LED) Pro Series |
|---|---|--|--|---|
| Overall Warranty | 3 Year | 3 Year | 3 Year | 3 Year |
| Maximum Screen Size | 21" x 24" (53 x 61 cm) | 23" x 31" (56 x 78.7 cm) | 47" x 31" (119.4 x 78.7 cm) or (2) 23" x 31" (56 x 78.7 cm) | 41" x 31" (104.1 x 78.7 cm) or (2) 20" x 24" (50.8 x 61 cm) |
| mage Area | 15" x 18" (38.1 x 45.7 cm) | 23" x 33" (58.42 x 83.3 cm) | 44" x 33" (111.8 x 83.3 cm) | 35" x 28" (88.9 x 71.1 cm) |
| Bulbs LED) | Qty. (3) 18" (61 cm) LED light bars | Qty. (5) 30" (76 cm) LED light bars (Optional 7 bars) | Qty. (11) 30" (76 cm) LED light bars | Qty. (7) 30" (76 cm) LED light bars |
| Bulbs Fluorescent) | Qty. (4) 20 watt T12-BL, black UV | Qty. (6) 40 watt F28T12\BLHO, Black UV fluorescent 28" (71cm) long | Qty. (12) 40 watt F28T12\BLHO, Black UV fluorescent 28" (71cm) long | N/A |
| Vacuum Pump, Oil-less Diaphragm | 1/16 HP 24 hg Max | 1/16 HP 24 hg Max | 1/4 HP High Output 23 Hg Max | 1/4 HP High Output 23 Hg Max |
| Power & Plug Spec nternational Available | 120V 3.5A NEMA 5-15P plug 240V 2A NEMA 6-15P plug | 120V / 60 HZ / 3.5A NEMA 5-15P 240V / 50/60 HZ / 2A NEMA 6-15P | 120V / 60 HZ / 6.5A (E4731) 120V / 60 HZ / 8A (E2-4731) NEMA 5-15P 240V / 50/60 HZ / 4A NEMA 6-15P | 120V / 60 HZ / 8A (E2-4731) NEMA 5-15P 240V / 50/60 HZ / 4A NEMA 6-15P |
| Overall Depth x Width x Height | Lid Closed 32.75" x 34.75" x 14" (83 x 88 x 36 cm) Lid Open 32.75" x 34.75" x 28" (83 x 88 x 71 cm) | Lid Closed 41.6 x 36.2 x 48.3" (105.7 x 92 x 122.7 cm) Lid Open 41.6 x 36.2 x 68.2" (105.7 x 92 x 173 cm) | Lid Closed 41.6 x 60.2 x 48.3" (105.7 x 153 x 122.7 cm) Lid Open 41.6 x 60.2 x 68.2" (105.7 x 153 x 173 cm) | Lid Closed 41.6 x 53.2.2 x 50.3" (105.7 x 135.1 x 127.8cm) Lid Open 41.6 x 53.2 x 70.2" (105.7 x 135.1 x 178.3 cm) |
| Overall Weight - Uncrated | 100 lbs (45.4 kg) | 180 lbs (81.6 kg) | 280 lbs (127 kg) | 325 lbs (147.4 kg) |
| Shipping Weight* | 223 lbs (101 kg) w/ Utility Cart (UC-1000) 483 lbs (219 kg) | 386 lbs (175 kg) w/ drying cabinet VDC253610 570 lbs (259 kg) | 494 lbs (224 kg) w/ drying cabinet VDC513610 851 lbs (386 kg) | 456 lbs (266.8 kg) |
| Shipping Dimensions* | 43" x 43" x 17" (109 x 109 x 43 cm) w/ Utility Cart (UC-1000) 43" x 43" x 35" (109 x 109 x 89 cm) | 48" x 45" x 47" (122 x114.3 x 79 cm) w/ drying cabinet VDC253610 49" x 45" x 49" (124 x 114 x 124 cm) | 69" x 48" x 47" (175 x 122 x 79 cm) w/ drying cabinet VDC513610 69" x 48" x 69" (175 x 122 x 124 cm) | 60" x 48" x 48" (152.4 x 122 x 122 cm) |

Drying Cabinets

Technical Specifications

| | Dri-Vault - Drying Cabinets | | | | |
|-----------------------------------|---|---|--|--|--|
| MADE IN U.S.A. | VDC-253610 | VDC-2536-24 | VDC-513610 | | |
| Defect Warranty | 3 Year | 3 Year | 3 Year | | |
| Maximum # of Screens | 10 @ maximum size | 24 @ maximum size | (10) @ 51" x 36" / (20) @ 25" x 36" | | |
| Maximum Screen Size | 25" x 36" x 1.625" (63.5 x 91.4 x 4.12 cm) | 25" x 36" x 1.625" (63.5 x 91.4 x 5.7 cm) | (10 screens) @ 51" x 36" (20 screens) @ 25" x 36" | | |
| Smallest Screen Width | 18" (46 cm) | 18" (46 cm) | No minimum size due to adjustable center tree | | |
| Blower (Free Air) | 177 CFM (5 cmm)120v or 290 CFM (8.2cmm) 240volt | 580 CFM (16.4 CMM) | 290 CFM (8.2 CMM) | | |
| Overall Depth x Width x Height | 39.5" (100 cm) x 34.75" (88 cm) x 29" (74 cm) / 32" (81 cm) w/ optional casters | 39.5" (100 cm) x 34.75" (88 cm) x 81" (206 cm) | 37.9" (96.3 cm) x 62.5" (159.1cm) x 32.3" (81.9cm) | | |
| Heater Wattage | 1,250 Watts 120 Volts or 1,550 Watts 240 Volts | 3,100 Watts 240 Volts | 1,550 Watts @ 240 Volts | | |
| Electrical Power | 120V / 10A / 1 Ph. / 60 HZ / NEMA 5-15P plug or 240V / 6A / 1 Ph. / 50/60 HZ / NEMA 6-15P plug | 240V / 16A / 1 Ph. / 50/60 HZ / NEMA 6-20P plug | 240V / 6A / 1 Ph. / 50/60 HZ / NEMA 6-15P plug | | |
| Shipping Weight* | 367 lbs (166.5 kg) | 670 lbs (303 kg) | 573 lbs (277 kg) | | |
| Shipping Dimensions* | 43" x 43" x 48" [109 x 109 x 122 cm] | 43" x 43" x 84" [109 x 109 x 213 cm] | 69" x 48" x 48" (175.3 x 122 x 122 cm) | | |

1 in = 2.54 cm 1 lb = 0.454 kg